

GALV. STEEL CORD FOR CONVEYOR BELTING

We supply hot-dipped galv. and electro-plating galv. steel cord for conveyor belting, our material has a good adhesion with rubber both after curing and after aging with our open construction and using 99.995% Zinc ingot, and we use water patenting to eliminating lead.



Construction	Dia.	Min.B/S	Density Kgs/100m	Construction	Dia.	Min.B/S	Density Kgs/100m
7×7 Open	3.0mm	9700N	3.47	7×19 Open	5.6mm	28980N	12.30
7×7 Open	3.2mm	10800N	3.92	7×19 Open	6.4mm	37400N	15.50
7×7 Open	3.3mm	11400N	4.30	7×19 Open	6.6mm	39500N	16.40
7×7 Open	3.4mm	12300N	4.55	7×19 Open	6.8mm	42700N	17.70
7×7 Open	3.6mm	13500N	5.10	7×19 Open	7.2mm	47100N	19.60
7×7 Open	4.1mm	17400N	6.66	7×19 Open	7.4mm	50600N	21.10
7×7 Open	4.3mm	19000N	7.36	7×19 Open	7.6mm	53000N	22.10
7×7 Open	4.6mm	23000N	8.27	7×19 Open	7.8mm	55100N	23.10
7×7 Open	5.0mm	25000N	9.73	7×19 Open	8.0mm	57200N	24.00
7×7 Open	5.2mm	26700N	10.50	7×19 Open	8.6mm	66100N	28.00
7×7 Open	5.3mm	27500N	10.90	7×19 Open	9.2mm	73900N	31.60
7×7 Open	5.4mm	28400N	11.50	7×19 Open	9.6mm	79700N	34.30
7×7 Open	5.7mm	30800N	12.80	7×19 Open	10.40mm	92500N	40.10

Wire rod:SWRH 72A,SWRH 82A

We also supply galv.steel cord,brass coated steel cord for rubber Track