

GALV. FINE CORD FOR PU TIMING BELT

We're one of the leading suppliers developed galv. fine cord for PU timing belt in China

Raw material:KSC 72,KSC82,
Kobe Steel,Japan

Our advantages:Extra high tensile strength, longer length without welding joints,lower elongation, less residual torsion and less oil residue.



Construction/ Dia. of wire	Cord Dia.	Length per spool	Min.B/S	Residual torsion
3×3×0.08mm	0.32mm	22000m	125N	+/-2turns
3×3×0.10mm	0.41mm	14000m	195N	+/-2turns
3×3×0.12mm	0.51mm	10000m	268N	+/-2turns
3×3×0.15mm	0.63mm	9000m	420N	+/-2turns
7×3×0.15mm	0.91mm	6000m	950N	+/-2turns
1×3+5×7×0.15mm	1.21mm	3500m	1740N	+/-2turns
1×19×0.12mm	0.60mm	9150m	620N	+/-2turns
7×7×0.15mm	1.35mm	3000m	1700N	+/-1turns
7×7×0.175mm	1.57mm	2000m	3200N	+/-1turns
8×7+1×19	1.5mm	3000m	2000N	+/-1turns

Oil residue:under 0.015%

Length in continuous length without welding joints

Primer coating as per customers'requirements